# thermo scientific

# Consistently pure water

for your clinical analyzers



# Designed to produce consistently pure water, to help you achieve fast, accurate test results

Thermo Scientific<sup>™</sup> Barnstead<sup>™</sup> clinical water purification systems feed your analyzers with reliable, pure water according to Clinical Laboratory Reagent Water (CLRW) standards.

- Reliable results
- Enhanced security with emergency bypass system
- Optimized for cost efficiency

These complete solutions are ready to use the day you receive your system, including everything from filters to accessories, for easy and economical ordering. All Barnstead clinical feed water systems feature an emergency bypass, designed to help you avoid any loss of production.

#### Trusted service when you need it

Your clinical analyzer runs all the time, so our clinical feed water systems are designed to do the same. If an issue arises, our service team is here to help get you back up and running. In most cases, service is available 24 hours a day, 7 days a week. Contact your Unity Lab Services representative or an authorized dealer for more information.

Barnstead clinical feed water systems offer innovative features that allow you to focus on your science.

#### Modular design

Upgrade from 60 L to 140 L by adding another RO membrane.

**Quick-connect consumables** Easily replace consumables, such as filters, with quick-connecters.

#### Fully automatic operation

Simply attach the potable tap water source to your system for it to begin automatic pure water production.

#### **Small footprints**

Free-standing units take up no bench space and can be easily relocated with bottom-mounted rollers.

All units are ready-to-use, equipped with installation kit, pre-filtration, UV-lamp, RO membranes, end filters and emergency bypass system.



#### Thermo Scientific<sup>™</sup> Barnstead<sup>™</sup> Pacific<sup>™</sup> AFT bench-top clinical feed water system

- Choice of 30 or 60 L tank, including recirculation/pressure pump and level control (UV lamp optional)
- Flow rates of 3,7,12,20 and 40 LPH at 15°C water temperature
- Emergency switch for security



Thermo Scientific<sup>™</sup> Barnstead<sup>™</sup> LabTower<sup>™</sup> AFT floor-standing clinical feed water system

- Integrated 100 L tank
- Large deionization canisters with 2800 L capacity at 10 °dH
- Flow rates of 20 and 40 LPH at 15°C water temperature
- Emergency switch for security



Thermo Scientific<sup>™</sup> Barnstead<sup>™</sup> MediTower<sup>™</sup> floor-standing clinical feed water system

- Integrated pressure tank with 20 L capacity (MediTower 140 has 2 tanks), including pressure pump
- Upgradeable from 60 to 140 L
- Large deionization canisters with 2000 L capacity at 10 °dH
- Flow rates of 60, 120 and 140 LPH at 15°C water temperature
- Emergency switch for security



## Continuous analysis of your samples

#### Emergency bypass system for enhanced security

Maximum operational security and reliability are standard due to an innovative bypass design. In the event of a system failure, you can easily flip a switch to transition to ion exchanger mode. The supply of high purity water is maintained without interruption and is independent of the other purification stages. An optional monitoring sensor is available with audible and visual alarms, as well as automatic system shut-off, if needed.

# thermo scientific

### Specifications

Thermo Scientific Barnstead Clinical Feed Water Systems				
Water System Specifications	Pacific AFT 3-40	LabTower AFT 20/40	MediTower 60/120/140	
Typical Conductivity	0.1-1.0	0.1-1.0	0.1-1.0	
Bacteria Removal	99%	99%	99%	
Rated Power (kW)	0.1	0.25	0.3	
Operating Voltage (V/Hz)	230/50 (115/60)	230/50 (115/60)	230/50 (115/60)	
Operating Pressure, (bar) min./max.	2/6	2/6	2/6	
Dimensions (W x D x H mm)	372 x 330 x 615	450 x 580 x 1500	560 x 660 x 1380	
Weight (kg)	24-26	66	150	

Feed Water Requirements				
Hardness	Hardness stabilized potable water			
Manganese and Iron	<0.05 mg/L			
Conductivity	<1000 µS/cm			
Free Chlorine Content	<0.1 mg/l			
Colloid Index Max.	3			
Temperature	1-30 °C			
Pressure	2-6 bar			

## Ordering Information

Pacific AFT	Clinical Feed Water Systems	Pacific AFT	Accessories and Consumables	
50135178	Pacific 3 LPH AFT with emergency switch, UV lamp	09.4011	Filter cartridge	
50135249	Pacific 7 LPH AFT with emergency switch, UV lamp	06.5201	Combi cartridge 5 µm + activated carbon - 10"	
50135250	Pacific 12 LPH AFT with emergency switch, UV lamp	06.5452	Hardness stabilizing unit - 10"	
50135264	Pacific 20 LPH AFT with emergency switch, UV lamp	50139226	Replacement UV lamp	
50135267	Pacific 40 LPH AFT with emergency switch, UV lamp	06.5031	Storage tank 30 liter as bench top with level-control	
LabTower A	<b>VFT Clinical Feed Water Systems</b>	00.0001	including pressure pump	
50135466	LabTower AFT 20 LPH with pre-treatment, storage tank 100 liters and pressure pump, emergency switch, UV lamp	06.5061	Storage tank 60 liter as bench top with level-control including pressure pump	
	LabTower AFT 40 LPH with pre-treatment, storage tank	06.5001	Sterile overflow for storage tank	
50135467	100 liters and pressure pump, emergency switch, UV lamp	06.5002	CO <sub>2</sub> Adsorber + vent filter for storage tank	
MediTower	Clinical Feed Water Systems	50135142	Sterile vent filter for storage tank	
Weunowei		06.5006	UV light for tank	
50130993	MediTower 60 LPH AFT with pressure tank 25 liters, degassing membrane, leak water sensor, UV lamp	06.5015	Wall-mounting for storage tank 30 liters	
	MediTower 120 LPH AFT with pressure tank 25 liters,	06.5016	Wall-mounting for storage tank 60 liters	
50131060	degassing membrane, leak water sensor, UV lamp	LabTower AFT Accessories and Consumables		
50134970	MediTower 140 LPH AFT with pressure tank 25 liters,	06.5204	Combi cartridge 5 µm + hardness stabilizing 10"	
50134970	degassing membrane, leak water sensor, UV lamp	50132714	Sterile overflow for storage tank	
Softener		50135142	Sterile vent filter for storage tank	
50130297	Mix Multi Mini Softener Capacity at 10° dH 2000 liters	50135141	Filter housing 10" for pressure outlet	
	d Pretreatment Accessories and Consumables	06.5101	Pre filter 1 µm - 10" for pressure outlet	
09.4000		06.5555	Sterile filter 0.2 µm – 10" for pressure outlet	
09.4000	Pre-treatment complete	09.1003	Sterile filter capsule 0.2 µm for dispenser	
06.2000				
10 0100	Bag of salt – 25 kg for softener	50139226	Replacement UV lamp for unit	
16.0129	Aqua-stop with magnetic valve	06.5006	Replacement UV lamp for unit UV light for storage tank	
06.1000	Aqua-stop with magnetic valve Hardness measuring kit	06.5006 09.5002	Replacement UV lamp for unit UV light for storage tank Replacement UV lamp for tank UV-housing no. 06.5006	
06.1000 <b>MediTower</b>	Aqua-stop with magnetic valve Hardness measuring kit Accessories and Consumables	06.5006	Replacement UV lamp for unit UV light for storage tank Replacement UV lamp for tank UV-housing no. 06.5006 DI 2800 ion exchange cartridge	
06.1000 <b>MediTower</b>	Aqua-stop with magnetic valve Hardness measuring kit Accessories and Consumables DI 2000 ion exchanger cartridge	06.5006 09.5002	Replacement UV lamp for unit UV light for storage tank Replacement UV lamp for tank UV-housing no. 06.5006 DI 2800 ion exchange cartridge 2 x 22 liters disposable resin for no. 02.2800 or 02.2800-	
06.1000 MediTower 02.2050-RDS 10.2017	Aqua-stop with magnetic valve Hardness measuring kit Accessories and Consumables DI 2000 ion exchanger cartridge 2 x 17 liters disposable resin for no. 02.2050 or 02.2050-RDS	06.5006 09.5002 02.2850-RDS	Replacement UV lamp for unit UV light for storage tank Replacement UV lamp for tank UV-housing no. 06.5006 DI 2800 ion exchange cartridge	
06.1000 MediTower 02.2050-RDS 10.2017 09.5002	Aqua-stop with magnetic valve Hardness measuring kit Accessories and Consumables DI 2000 ion exchanger cartridge 2 x 17 liters disposable resin for no. 02.2050 or 02.2050-RDS Replacement UV lamp	06.5006 09.5002 02.2850-RDS	Replacement UV lamp for unit UV light for storage tank Replacement UV lamp for tank UV-housing no. 06.5006 DI 2800 ion exchange cartridge 2 x 22 liters disposable resin for no. 02.2800 or 02.2800-	
06.1000 MediTower 02.2050-RDS 10.2017	Aqua-stop with magnetic valve Hardness measuring kit Accessories and Consumables DI 2000 ion exchanger cartridge 2 x 17 liters disposable resin for no. 02.2050 or 02.2050-RDS	06.5006 09.5002 02.2850-RDS	Replacement UV lamp for unit UV light for storage tank Replacement UV lamp for tank UV-housing no. 06.5006 DI 2800 ion exchange cartridge 2 x 22 liters disposable resin for no. 02.2800 or 02.2800-	

06.5555 Sterile filter 0.2 µm

### Find out more at thermofisher.com/purewater

© 2016 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries unless otherwise specified. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Australia +61 39757 4300 Austria +43 1 801 40 0 Belgium +32 53 73 42 41 China +800 810 5118 or +400 650 5118 France +33 2 2803 2180 Germany national toll free 0800 1 536 376 Germany international +49 6184 90 6321 India toll free 1800 22 8374 India +91 22 6716 2200 Italy +39 02 95059 552 Japan +81 3 5826 1616 Netherlands +31 76 579 55 55 New Zealant +64 9 980 6700 Nordic/Baltic/CIS countries +358 10 329 2200 Russia +7 812 703 42 15 Spain/Portugal +34 93 223 09 18 Switzerland +41 44 454 12 12 UK/Ireland +44 870 609 9203 USA/Canada +1 866 984 3766

**Other Asian countries** +852 3107 7600 **Countries not listed** +49 6184 90 6000

